

24/7
Round the Clock
Service & Support

We Ensure
NONSTOP
POWER

SAVE POWER
EXCELLENCE IN ENERGY

Flat B-6, House 14/A, Road 2/2, Banani, Dhaka-1213.
Phone: 88 02 8837275 | Hotline: + 88 01907 999 666 | E-mail: savepowerbangladesh@gmail.com
Web: www.savepowerbd.com



SILENT DIESEL ENGINE GENERATOR

50 HZ AT 1500 RPM

Save Power Bangladesh

Flat B-6, House 14/A, Road 2/2, Banani, Dhaka-1213.
Phone: +88 02 8837275 | Hotline: +88 01907 999 666
E-mail: savepowerbangladesh@gmail.com
Web: www.savepowerbd.com

24/7
Round the Clock

Service & Support

Perkins®

PERKINS

SILENT DIESEL
ENGINE GENERATOR

Perkins is the most popular brand in Bangladesh. The newly designed sturdy canopies or the containerised enclosures both maximise noise reduction which makes any sound attenuated unit suitable for construction sites or home backup power. Our standard Stamford, Meccalte, Leroy Somer Alternator & Deepsea control panel.



PERKINS SERIES SPECIFICATION					General Specification								
GENTSETS	Specifications 50HZ 400-230V				Engine Type	CYL	DSPL (L)	Fuel Cons 75% L/h	Tank capacity [L]	Compact Version			
	KVA/KW Cos 0.8									Dimension LxLWxH [mm]	Weight kg	Noise db(A)	
	Prime Power		Standby Power										
	KVA	KW	KVA	KW									
	20	16	22	17.6	404A-22G1	3	2.216	4	50	1600x700x1050	570	68	
	30	24	33	26.4	1103A-33G	4	3.3	5.4	75	2000x850x1275	880	68	
	45	36	50	40	1103A-33TG1	3	3.3	8	75	2000x850x1275	945	68	
	60	48	66	52.8	1103A-33TG2	3	3.3	10.4	75	2000x850x1275	990	68	
	80	64	88	70	1104A-44TG2	3	4.4	14	120	2300x1050x1550	1325	69	
	100	80	110	88	1104C-44TAG2	4	4.4	17.1	120	2300x1050x1550	1440	69	
	135	108	149	119	1106A-70TG1	4	7.01	22.1	250	3200x1100x2000	2000	69	
	150	120	165	132	1106A-70TAG2	6	7.01	24.7	250	3200x1100x2000	2050	69	
	180	144	198	158	1106A-70TAG3	6	7.01	31.8	250	3200x1100x2000	2100	69	
	200	160	220	176	1106A-70TAG4	6	7.01	35.5	250	3200x1100x2000	2200	69	
	230	184	253	202	1506A-E88TAG2	6	8.5	36	250	3700x1450x2200	2350	69	
	250	200	275	220	1506A-E88TAG3	6	8.8	42	250	3700x1450x2200	2550	69	
	275	220	302.5	242	1506A-E88TAG4	6	8.8	46	250	3700x1450x2200	3000	69	
	300	240	330	264	1506A-E88TAG5	6	8.8	48	400	3700x1450x2200	3000	70	
	350	280	385	308	2206A-E13TAG2	6	12.5	54	400	4850x1850x2580	4200	70	
	400	320	440	352	2206A-E13TAG3	6	12.5	62	400	4850x1850x2580	4250	70	
	450	360	495	396	2506C-E15TAG1	6	15.2	72	400	4850x1850x2580	4300	70	
	500	400	550	440	2506C-E15 iTAG2	6	15.2	76	400	4850x1850x2580	4900	70	

24/7
Round the Clock

Service & Support

SAVE POWER
EXCELLENCE IN ENERGY

ISUZU

ISUZU
SILENT DIESEL
ENGINE GENERATOR

ISUZU Generator is environment friendly and economical with low fuel consumption which is at leading level than other competitive products. The Isuzu generator is Lightweight and compact, with outstanding quiet performance.

ISUZU Engines adopt advanced design to achieve higher horsepower and Highly rated around the world for reliability and durability. Our standard Stamford, Kawise, alternator & Deepsea control panel.



ISUZU SERIES SPECIFICATION

GENTSETS	Specifications 50HZ 400-230V				General Specification							
	KVA/KW Cos 0.8				Engine Type	CYL	DSPL (L)	Fuel Cons 75 % L/h	Tank Capacity	Compact Version		
	Prime Power		Standby Power							Dimension	Weight	Noise
	KVA	KW	KVA	KW						L x W x H (mm)	kg	db(A)
SPB-25IS	25	20	27		JE493DB-02	4L	2.771	3.7	64	2050x905x1060	850	68
SPB-30IS	30	24	33		JE493DB-02	4L	2.771	4.1	64	2050x905x1060	862	68
SPB-40IS	40	32	45		JE493ZLDB-02	4L	2.771	4.5	80	2150x905x1060	910	68
SPB-45IS	50	40	55		JE493GTB	4L	2.771	4.5	88	2150x905x1060	950	68

24/7
Round the Clock

Service & Support

SAVE POWER
EXCELLENCE IN ENERGY



RICARDO

SILENT DIESEL ENGINE GENERATOR

Ricardo is a worldwide renowned engine brand for power generation. With the Stamford, Kawise type alternator this series has become a reliable model of generating set in Bangladesh. It has the smartgen controller to controlling the generating set as well as it secure the engine from any unexpected Occurrence.



RICARDO SERIES SPECIFICATION					General Specification							
GENTSETS	Specifications 50HZ 400-230V				Engine Type	CYL	DSPL (L)	Fuel Cons 75% L/h	Tank capacity	Compact Version		
	KVA/KW Cos 0.8									Dimension L x W x H (mm)	Weight kg	Noise db(A)
	Prime Power		Standby Power									
	KVA	KW	KVA	KW								
	25	20	28	22	495D	4	2.75	2.5	8 hours base fuel tank	2000*900*1200	850	68
	30	24	33	26.4	4100D	4	3.1	3		2100*900*1200	850	68
	40	32	44	35.2	K4100DS	4	3.61	3.5		2250*1000*1300	950	70
	50	40	55	44	K4100ZDS	4	3.98	4		2250*1000*1300	990	70
	62.5	50	65.5	55	R4105ZDS	4	4.33	5		2300*1050*1300	1050	70
	72.5	58	80	64	R6105ZDS	6	6.49	6		2500*1150*1400	1100	70
	100	80	110	88	R6105AZLDS	6	6.49	8		2500*1150*1400	1170	70
	125	100	150	120	R6105BZLDS	6	6.49	9		2800*1150*1380	1200	70
	150	120	187.5	150	R6110ZLDS	6	7.52	10		2800*1150*1380	1300	75
	187.5	150	212.5	170	6126-68D	6	8.82	12		2800*1150*1380	1500	75
	200	160	250	200	6126-42D	6	8.82	14		2900*1300*1850	1650	75
	250	200	275	220	6126A-260D	6	9.83	16		2900*1300*1850	1700	75
	325	260	362.5	290	WT12D-308	6	11.59	18		3150*1500*1950	1800	75
	350	280	387.5	310	WT13-330D	6	13.24	20		3300*1600*1950	2900	75

24/7
Round the Clock

Service & Support

Environment-Friendly

- ▶ We pay special attention to environmental function when we design our gensets.
- ▶ High-strength material and advanced design minimized vibration.
- ▶ We adopt advanced noise reduction measures and equipment and keep the genset running in a quiet state, while not affecting the daily life and work.
- ▶ The application of anti-vibration mounting keeps the vibration of the genset under control, lowering its noise level meanwhile increasing the life span of genset.



Easy to operate

- ▶ Water feeder is located on top of the canopy, and water can be easily filled through the tube.
- ▶ External quick connection helps easily realize monitor the mains, ATS transfer.
- ▶ Then daily maintenance work can be performed on the two sides of the machine, and a wide door allows you easily get in the machine. With lock fixed on the control panel, the door can be locked during genset unused or running.



Easy

Standard Control Function

- ▶ Start/ stop engine optional
- ▶ Low oil pressure (shutdown)
- ▶ High water temperature (shutdown)
- ▶ Charge failure (shutdown)
- ▶ Over speed (shutdown)
- ▶ Over voltage (shutdown)
- ▶ Over frequency (shutdown)
- ▶ Low water level (shutdown)
- ▶ Auxiliary shutdown (optional)

Standard Features

- ▶ Anti-vibration mounting between engine/ alternator and base-plate
- ▶ 12-Volt starter battery and leads
- ▶ Control panel containing an output circuit breaker with thermal overloaded protection and electric control module with digital display.
- ▶ Emergency stop button (lockdown type)
- ▶ Operations Handbook
- ▶ Electrical diagram

About Us

Save Power provides a wide range of high-quality Products and services geared to our customers specific needs and requirements. As a service provider of your energy equipment, we ensure the high standards and super or performance. Our products have a good performance in quality. We have a very good relationship with Cummins, Perkins, Kubota, Deutz, Lovol, Isuzu, Mitsubishi, and Ricardo engines, which ensure high-technology generators. Also, we pay special attention to our technology innovation and quality control. To ensure the quality of our products, CNC machines, pretreatment and powder coating facilities for the steel frame and silent canopy have been put into use in our base.

We want to be a part of your energy solutions and hope that will bring mutual benefit to both parties in the near future.

After Sales Service

- Hassle-free 24/7 round the clock after sales support
- Fast and responsive service support staffs
- A comprehensive range of spare parts
- Availability of spare parts
- Refurbishment and upgrade of systems
- Fastest Installation